



4550 Post Oak Place, Suite 202
 Houston, Texas 77027
 Phone: (713) 623-6900 * Fax: (713) 623-6905
 Web: www.qualitybit.com
 E-mail: quality@qualitybit.com

Rig 2 Inventory Summary

(Updated 08-16-08; Note - Inventory Subject to Change)

Carrier:	IRI 1999 RD-20, RANGE II, 4 Axle Carrier w/ Cummins Q5K19 305 HP Diesel Engine, Eaton Fuller 8-Speed Transimission w/ Jacobs Brake, Twin No-Spin Rear Axles, 226" WB, 86,000 GVWR, (3) Hydraulic Leveling Jacks, T/A Rear w/ 11R22.5 Tires, Spoke Wheels, T/A Single Tire Front Axles w/ 65R22.5 Tires, Spoke Wheels, also has the attached 7 joint carousel.
Power Pack:	Cummins Q5K19C Diesel Engine, 700 HP, Ingersoll-Rand HR2.5 Over/Under Screw Air End, 1250/350 CFM @ 1800 RPM
Mast:	IRI Mast Rated @ 110,000 Lbs w/ 30,000 Pull-Down 51'H
Feed System:	Pullback=110,000 Lb., Pulldown=30,000 Lb., Drill Feed Rate=22 Fpm., Fast Feed Down=154 Fpm.
Rotary Head:	4SF-2-10 Spur Gear Head, 0-110 RPM., 8,000 Lb. Torque, 3" Circulating Piping rated @ 1,500 Psi. WP.
Jib Hoist & Boom:	Lifting Capacity of 4,000 Lb.(Bare Drum), Line Speed=110 Fpm.(Bare Drum)
Casing Hoist:	Lift Capacity of 7,500 Lb. Max., Line Speed=60 Fpm. Max.
Substructure:	4'H x 40'L Back-on w/ 6' x 6' Work Platform
Dog House / Fuel Tank:	Shop Built 8'W x 12'L Dog House & 3,400 Gal. Fuel Tank Mounted on 40'L T/A Trailer, 10 Hole Budd Wheels, 11R24.5 Tires (1) 210 Bbl. Vertical Water Storage Tank
Wireline Unit:	Halliburton Wireline Unit w/ 12,000 Ft. of .092 wire.
Trailers:	(1) 30' Float Trailer
Ancillary Equipment:	Pipe Tub - (1) w/ Center Walk
Tubulars:	Drill Rod - 176 Jts. - 4 1/2" Drill Rod w/ 2 7/8" IF BxP Connections,